



Hydronics Depot Inc.
Official Distributor of ODE Italy

Series 21ENN SOLENOID VALVE

Series 21ENN

2-way, internally piloted, normally closed solenoid valve

1/4"-1/2"

Pipe Sizes

8W, 12W, 14W

Coils

2-300 psi

Operating Pressure



Materials Construction

Body:	Brass
Armature Tube:	Stainless Steel 300
Fixed Core:	Stainless Steel 400
Plunger:	Stainless Steel 400
Spring:	Stainless Steel 300
Shading Ring:	Copper

Electrical Connection

Rating	NEMA 4
Strain Relief Connector	CAGDIN/01
1/2" Conduit Connector	CONDIN/02
6 ft. Power Cord	PCC6FT/03

Note: For more detailed information, please contact us at info@odecanada.com



Hydronics Depot Inc.
Official Distributor of ODE Italy

Series 21ENN SOLENOID VALVE

Sealing Material	Temperature Range	Medium Examples
FKM	14° – 280°F	Air, Inert Gas, Water, Synthetic oils

Model	Pipe Size (inch)	Orifice Size (Inch)	Flow Factor (CV)	Watt Rating (W)	Min Pressure (PSI)	Max Pressure (AC)	Max Pressure (DC)	Voltage (AC / DC)
21EN2KOV105N	1/4"	7/16"	1.5	8	2	300	150	12,24,110,220
21EN2KOV105N	1/4"	7/16"	1.5	12	2	300	300	12,24,110,220
21EN2KOV105N	1/4"	7/16"	1.5	14	2	300	300	12,24,110,220
21EN3KOV105N	3/8"	7/16"	1.7	8	2	300	150	12,24,110,220
21EN3KOV105N	3/8"	7/16"	1.7	12	2	300	300	12,24,110,220
21EN3KOV105N	3/8"	7/16"	1.7	14	2	300	300	12,24,110,220
21EN4KOV105N	1/2"	7/16"	1.7	8	2	300	150	12,24,110,220
21EN4KOV105N	1/2"	7/16"	1.7	12	2	300	300	12,24,110,220
21EN4KOV105N	1/2"	7/16"	1.7	14	2	300	300	12,24,110,220

Note: For more detailed information, please contact us at info@odecanada.com