



Hydronics Depot Inc.
Official Distributor of ODE Italy

Series 21WN3-4N SOLENOID VALVE

Series 21WN3-4N

2-way, internally piloted, normally closed solenoid valve

3/8"-1/2"

Pipe Sizes

8W

Coil

2-230 psi

Operating Pressure



Materials Construction

| | |
|----------------|---------------------|
| Body: | Brass |
| Armature Tube: | Stainless Steel 300 |
| Fixed Core: | Stainless Steel 400 |
| Plunger: | Stainless Steel 400 |
| Spring: | Stainless Steel 300 |
| Shading Ring: | Copper |

Electrical Connection

| | |
|-------------------------|-----------|
| Rating | NEMA 4 |
| Strain Relief Connector | CAGDIN/01 |
| ½" Conduit Connector | CONDIN/02 |
| 6 ft. Power Cord | PCC6FT/03 |

Note: For more detailed information, please contact us at info@odecanada.com



Hydronics Depot Inc.
Official Distributor of ODE Italy

Series 21WN3-4N SOLENOID VALVE

| Sealing Material | Temperature Range | Medium Examples |
|------------------|-------------------|---------------------------------------|
| FKM | 14° – 280°F | Air, Inert Gas, Water, Synthetic oils |

| Model | Pipe Size (inch) | Orifice Size (Inch) | Flow Factor (CV) | Watt Rating (W) | Min Pressure (PSI) | Max Pressure (AC) | Max Pressure (DC) | Voltage (AC / DC) |
|--------------|---------------------|------------------------|---------------------|--------------------|-----------------------|----------------------|----------------------|------------------------|
| 21WN3K0V130N | 3/8" | 1/2" | 4.1 | 8 | 2 | 230 | 230 | 12,24,110,220 |
| 21WN4K0V130N | 1/2" | 1/2" | 4.8 | 8 | 2 | 230 | 230 | 12,24,110,220 |

Note: For more detailed information, please contact us at info@odecanada.com