



Hydronics Depot Inc.  
Official Distributor of ODE Italy

## Series 21WN3-4N

### SOLENOID VALVE

## Series 21WN3-4N

2-way, internally piloted, normally closed solenoid valve

**3/8"-1/2"**

Pipe Sizes

**8W**

Coil

**2-230 psi**

Operating Pressure



### Materials Construction

Body:	Brass
Armature Tube:	Stainless Steel 300
Fixed Core:	Stainless Steel 400
Plunger:	Stainless Steel 400
Spring:	Stainless Steel 300
Shading Ring:	Copper

### Electrical Connection

Rating	NEMA 4
Strain Relief Connector	CAGDIN/01
½" Conduit Connector	CONDIN/02
6 ft. Power Cord	PCC6FT/03

**Note:** For more detailed information, please contact us at [info@odecanada.com](mailto:info@odecanada.com)



Hydronics Depot Inc.  
Official Distributor of ODE Italy

## Series 21WN3-4N SOLENOID VALVE

Sealing Material	Temperature Range	Medium Examples
FKM	14° – 280°F	Air, Inert Gas, Water, Synthetic oils

Model	Pipe Size (inch)	Orifice Size (Inch)	Flow Factor (CV)	Watt Rating (W)	Min Pressure (PSI)	Max Pressure (AC)	Max Pressure (DC)	Voltage (AC / DC)
21WN3KOV130N	3/8"	1/2"	4.1	8	2	230	230	12,24,110,220
21WN4KOV130N	1/2"	1/2"	4.8	8	2	230	230	12,24,110,220

**Note:** For more detailed information, please contact us at [info@odecanada.com](mailto:info@odecanada.com)