



Hydronics Depot Inc.
Official Distributor of ODE Italy

Series 21WN3Z-4Z SOLENOID VALVE

Series 21WN3Z-4Z

2-way, internally piloted, normally open solenoid valve

3/8"-1/2"

Pipe Sizes

8W

Coil

2-230 psi

Operating Pressure



Materials Construction

Body:	Brass
Armature Tube:	Stainless Steel 300
Fixed Core:	Stainless Steel 400
Plunger:	Stainless Steel 400
Spring:	Stainless Steel 300
Shading Ring:	Copper

Electrical Connection

Rating	NEMA 4
Strain Relief Connector	CAGDIN/01
1/2" Conduit Connector	CONDIN/02
6 ft. Power Cord	PCC6FT/03

Note: For more detailed information, please contact us at info@odecanada.com



Hydronics Depot Inc.
Official Distributor of ODE Italy

Series 21WN3Z-4Z SOLENOID VALVE

Sealing Material	Temperature Range	Medium Examples
FKM	14° – 280°F	Air, Inert Gas, Water, Synthetic oils

Model	Pipe Size (inch)	Orifice Size (Inch)	Flow Factor (CV)	Watt Rating (W)	Min Pressure (PSI)	Max Pressure (AC)	Max Pressure (DC)	Voltage (AC / DC)
21WN3Z0V130	3/8"	1/2"	4.1	8	2	230	230	12,24,110,220
21WN4Z0V130	1/2"	1/2"	4.8	8	2	230	230	12,24,110,220

Note: For more detailed information, please contact us at info@odecanada.com



Hydronics Depot Inc.
Official Distributor of ODE Italy

Series 21WN3Z-4Z

SOLENOID VALVE

Sealing Material	Temperature Range	Medium Examples
NBR	14° – 195°F	Air, Inert gas, Water

Model	Pipe Size (inch)	Orifice Size (Inch)	Flow Factor (CV)	Watt Rating (W)	Min Pressure (PSI)	Max Pressure (AC)	Max Pressure (DC)	Voltage (AC / DC)
21WN3Z0B130	3/8"	1/2"	4.1	8	2	230	230	12,24,110,220
21WN4Z0B130	1/2"	1/2"	4.8	8	2	230	230	12,24,110,220

Note: For more detailed information, please contact us at info@odecanada.com