



Hydronics Depot Inc.
Official Distributor of ODE Italy

Series 21WN5-9MR SOLENOID VALVE

Series 21WN5-9MR

2-way, internally piloted, normally closed solenoid valve

3/4" -2"

Pipe Sizes

8W

Coil

2-230 psi

Operating Pressure



Materials Construction

Body:	Brass
Armature Tube:	Stainless Steel 300
Fixed Core:	Stainless Steel 400
Plunger:	Stainless Steel 400
Spring:	Stainless Steel 300
Shading Ring:	Copper

Electrical Connection

Rating	NEMA 4
Strain Relief Connector	CAGDIN/01
½" Conduit Connector	CONDIN/02
6 ft. Power Cord	PCC6FT/03

Note: For more detailed information, please contact us at info@odecanada.com



Hydronics Depot Inc.
Official Distributor of ODE Italy

Series 21WN5-9MR SOLENOID VALVE

Sealing Material	Temperature Range	Medium Examples
FKM	14° – 280°F	Air, Inert Gas, Water, Synthetic oils

Model	Pipe Size (inch)	Orifice Size (Inch)	Flow Factor (CV)	Watt Rating (W)	Min Pressure (PSI)	Max Pressure (AC)	Max Pressure (DC)	Voltage (AC / DC)
21WN5KV190MR	3/4"	3/4"	9.8	8	2	230	230	12,24,110,220
21WN6KV250MR	1"	1"	14	8	2	230	230	12,24,110,220
21WN7KV350MR	1 1/4"	1 3/8"	28	8	2	150	150	12,24,110,220
21WN8KV400MR	1 1/2"	1 1/2"	36	8	2	150	150	12,24,110,220
21WN9KV500MR	2"	2"	53	8	2	150	150	12,24,110,220

Note: For more detailed information, please contact us at info@odecanada.com



Hydronics Depot Inc.
Official Distributor of ODE Italy

Series 21WN5-9MR SOLENOID VALVE

Sealing Material	Temperature Range	Medium Examples
NBR	14° – 195°F	Air, Inert Gas, Water

Model	Pipe Size (inch)	Orifice Size (Inch)	Flow Factor (CV)	Watt Rating (W)	Min Pressure (PSI)	Max Pressure (AC)	Max Pressure (DC)	Voltage (AC / DC)
21WN5KB190MR	3/4"	3/4"	9.8	8	2	230	230	12,24,110,220
21WN6KB250MR	1"	1"	14	8	2	230	230	12,24,110,220
21WN7KB350MR	1 1/4"	1 3/8"	28	8	2	150	150	12,24,110,220
21WN8KB400MR	1 1/2"	1 1/2"	36	8	2	150	150	12,24,110,220
21WN9KB500MR	2"	2"	53	8	2	150	150	12,24,110,220

Note: For more detailed information, please contact us at info@odecanada.com