



Hydronics Depot Inc.  
Official Distributor of ODE Italy

## Series 21WN3Z-4Z

### SOLENOID VALVE

## Series 21WN5Z-9Z

2-way, internally piloted, normally open solenoid valve

**3/4"-2"**

Pipe Sizes

**8W**

Coil

**2-230 psi**

Operating Pressure

Missing  
Picture

### Materials Construction

Body:	Brass
Armature Tube:	Stainless Steel 300
Fixed Core:	Stainless Steel 400
Plunger:	Stainless Steel 400
Spring:	Stainless Steel 300
Shading Ring:	Copper

### Electrical Connection

Rating	NEMA 4
Strain Relief Connector	CAGDIN/01
½" Conduit Connector	CONDIN/02
6 ft. Power Cord	PCC6FT/03

**Note:** For more detailed information, please contact us at [info@odecanada.com](mailto:info@odecanada.com)



Hydronics Depot Inc.  
Official Distributor of ODE Italy

## Series 21WN3Z-4Z

### SOLENOID VALVE

Sealing Material	Temperature Range	Medium Examples
FKM	14° – 280°F	Air, Inert Gas, Water, Synthetic oils

Model	Pipe Size (inch)	Orifice Size (Inch)	Flow Factor (CV)	Watt Rating (W)	Min Pressure (PSI)	Max Pressure (AC)	Max Pressure (DC)	Voltage ( AC / DC )
21WN5ZV190	3/4"	3/4"	9.8	8	2	230	230	12,24,110,220
21WN6ZV250	1"	1"	14	8	2	230	230	12,24,110,220
21WN7ZV350	1 1/4"	1 3/8"	28	8	2	150	150	12,24,110,220
21WN8ZV400	1 1/2"	1 1/2"	36	8	2	150	150	12,24,110,220
21WN9ZV500	2"	2"	52	8	2	150	150	12,24,110,220

**Note:** For more detailed information, please contact us at [info@odecanada.com](mailto:info@odecanada.com)



Hydronics Depot Inc.  
Official Distributor of ODE Italy

## Series 21WN3Z-4Z

### SOLENOID VALVE

Sealing Material	Temperature Range	Medium Examples
NBR	14° – 195°F	Air, Inert gas, Water

Model	Pipe Size (inch)	Orifice Size (Inch)	Flow Factor (CV)	Watt Rating (W)	Min Pressure (PSI)	Max Pressure (AC)	Max Pressure (DC)	Voltage ( AC / DC )
21WN5ZB190	3/4"	3/4"	9.8	8	2	230	230	12,24,110,220
21WN6ZB250	1"	1"	14	8	2	230	230	12,24,110,220
21WN7ZB350	1 1/4"	1 3/8"	28	8	2	150	150	12,24,110,220
21WN8ZB400	1 1/2"	1 1/2"	36	8	2	150	150	12,24,110,220
21WN9ZB500	2"	2"	52	8	2	150	150	12,24,110,220

**Note:** For more detailed information, please contact us at [info@odecanada.com](mailto:info@odecanada.com)



Hydronics Depot Inc.  
Official Distributor of ODE Italy

## Series 21WN3Z-4Z SOLENOID VALVE

Sealing Material	Temperature Range	Medium Examples
EPDM	14° – 280°F	Water, Low-pressure steam

Model	Pipe Size (inch)	Orifice Size (Inch)	Flow Factor (CV)	Watt Rating (W)	Min Pressure (PSI)	Max Pressure (AC)	Max Pressure (DC)	Voltage ( AC / DC )
21WN5ZE190	3/4"	3/4"	9.8	8	2	230	230	12,24,110,220
21WN6ZE250	1"	1"	14	8	2	230	230	12,24,110,220
21WN7ZE350	1 1/4"	1 3/8"	28	8	2	150	150	12,24,110,220
21WN8ZE400	1 1/2"	1.5	36	8	2	150	150	12,24,110,220
21WN9ZE500	2"	2"	52	8	2	150	150	12,24,110,220

**Note:** For more detailed information, please contact us at [info@odecanada.com](mailto:info@odecanada.com)