



Hydronics Depot Inc.
Official Distributor of ODE Italy

Series 21YN-Z-YW SOLENOID VALVE

Series 21WN3Z-4Z

2-way, internally piloted, normally open solenoid valve

3/8"-1/2"

Pipe Sizes

8W

Coil

2-230 psi

Operating Pressure



Materials Construction

Body:	Brass
Armature Tube:	Stainless Steel 300
Fixed Core:	Stainless Steel 400
Plunger:	Stainless Steel 400
Spring:	Stainless Steel 300
Shading Ring:	Copper

Electrical Connection

Rating	NEMA 4
Strain Relief Connector	CAGDIN/01
½" Conduit Connector	CONDIN/02
6 ft. Power Cord	PCC6FT/03

Note: For more detailed information, please contact us at info@odecanada.com



Hydronics Depot Inc.
Official Distributor of ODE Italy

Series 21XN-Z-YW SOLENOID VALVE

Sealing Material	Temperature Range	Medium Examples
PTFE	-40° – 360°F	Air, Inert Gas, Water, Synthetic oils

Model	Pipe Size (inch)	Orifice Size (Inch)	Flow Factor (CV)	Watt Rating (W)	Min Pressure (PSI)	Max Pressure (AC)	Max Pressure (DC)	Voltage (AC / DC)
21YN4ZOT130-YW	1/2"	1/2"	3.4	8	13	150	150	12,24,110,220
21YN5ZOT190-YW	3/4"	3/4"	6.2	8	13	150	150	12,24,110,220
21YN6ZOT250-YW	1"	1"	11	8	13	150	150	12,24,110,220

Note: For more detailed information, please contact us at info@odecanada.com