



Hydronics Depot Inc.  
Official Distributor of ODE Italy

## Series 21YN-YW SOLENOID VALVE

### Series 21YN-YW

2-way, normally closed, brass body solenoid valve,  
for hot water/steam service

**1/2"-1"**

Pipe Sizes

**8W**

Coil

**13-150 psi**

Operating Pressure



#### Materials Construction

Body:	Brass
Armature Tube:	Stainless Steel 300
Fixed Core:	Stainless Steel 400
Plunger:	Stainless Steel 400
Spring:	Stainless Steel 300
Shading Ring:	Copper

#### Electrical Connection

Rating	NEMA 4
Strain Relief Connector	CAGDIN/01
½" Conduit Connector	CONDIN/02
6 ft. Power Cord	PCC6FT/03

**Note:** For more detailed information, please contact us at [info@odecanada.com](mailto:info@odecanada.com)



Hydronics Depot Inc.  
Official Distributor of ODE Italy

## Series 21YN-YW SOLENOID VALVE

Sealing Material	Temperature Range	Medium Examples
PTFE	-40° – 360°F	Steam, Hot Water, Chemicals*

Model	Pipe Size (inch)	Orifice Size (Inch)	Flow Factor (CV)	Watt Rating (W)	Min Pressure (PSI)	Max Pressure (AC)	Max Pressure (DC)	Voltage ( AC / DC )
21YN4K0T130-YW	1/2"	1/2"	3.4	8	13	150	150	12,24,110,220
21YN5K0T190-YW	3/4"	3/4"	6.2	8	13	150	150	12,24,110,220
21YN6K0T250-YW	1"	1"	11	8	13	150	150	12,24,110,220

\* Minimum fluid temperature of 140° F is recommended for optimal sealing

**Note:** For more detailed information, please contact us at [info@odecanada.com](mailto:info@odecanada.com)